Genie® GS™-2669 RT, GS-3369 RT & GS-4069 RT

Specifications

Models	GS-2669 RT		GS-3369 RT		GS-4069 RT	
Measurements	**US**	**Metric**	**US**	**Metric**	**US**	**Metric**
Working height max.(1)	32 ft 2 in	10 m	38 ft 8 in	11.96 m	46 ft 3 in	14.3 m
A Platform height max.	26 ft 2 in	8 m	32 ft 8 in	9.96 m	40 ft 3 in	12.3 m
B Platform height - stowed	4 ft 10 in	1.47 m	4 ft 10 in	1.47 m	5 ft 5 in	1.65 m
C Platform length - outside	9 ft 2 in	2.79 m	9 ft 2 in	2.79 m	9 ft 2in	2.79 m
Platform length - outside, extended	14 ft 2 in	4.32 m	14 ft 2 in	4.32 m	14 ft 2 in	4.32 m
Slide-out platform extension deck - length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
D Platform width - outside	5 ft 3 in	1.60 m	5 ft 3 in	1.60 m	5 ft 3 in	1.60 m
Toeboard height	6 in	15 cm	6 in	15 cm	6 in	15 cm
E Height - stowed (folding rails)(2)	8 ft 6 in	2.59 m	8 ft 6 in	2.59 m	9 ft	2.74 m
Height - stowed (rails lowered)	6 ft 3.5 in	1.92 m	6 ft 3.5 in	1.92 m	6 ft 10 in	2.08 m
F Length machine - stowed	10 ft 3 in	3.12 m	10 ft 3 in	3.12 m	10 ft 3 in	3.12 m
Length machine - stowed, extended	14 ft 9 in	4.5 m	14 ft 9 in	4.5 m	14 ft 9 in	4.5 m
Length machine - with outriggers	12 ft 4 in	3.76 m	12 ft 4 in	3.76 m	12 ft 4 in	3.76 m
G Width	5 ft 9 in	1.75 m	5 ft 9 in	1.75 m	5 ft 9 in	1.75 m
H Wheelbase	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m
I Ground clearance (center)	9.5 in	24 cm	9.5 in	24 cm	9.5 in	24 cm
Productivity						
Max. platform occupancy (in/out)	4/4		4/2		3/2	
Lift capacity	1,500 lb	680 kg	1,000 lb	454 kg	800 lb	363 kg
Lift capacity - extension deck extended	300 lb	136 kg	300 lb	136 kg	300 lb	136 kg
Max. platform drive height	26 ft 2 in	5.85 m	32 ft 8 in	9.96 m	40 ft 3 in	12.3 m
Drive speed - stowed	3.5 mph	5.6 km/h	3.5 mph	5.6 km/h	3.5 mph	5.6 km/h
Drive speed - raised	0.3 mph	0.5 km/h	0.3 mph	0.5 km/h	0.3 mph	0.5 km/h
Gradeability - stowed(3)	40 %		35 %		35 %	
Turning radius - inside/outside	83 in/181.2 in	2.11 m/4.6 m	83 in/181.2 in	2.11 m/4.6 m	83 in/181.2 in	2.11 m/4.6 m
Lifting speed - raise/lower	34/31 sec		39/29 sec		61/28 sec	
Tilt sensor activation (front to back/side to side)	3° / 2°		3° / 2°		3° / 2°	
Max. outrigger leveling (front to back /side to side)	5.3° / 11.7°		5.3° / 11.7°		5.3° / 11.7°	
Drive						
Tires - Foam-filled rough terrain	12×26 in	30×66 cm	12×26 in	30×66 cm	12×26 in	30×66 cm
Power						
Power	Diesel		Diesel		Diesel	
Fuel Tank	10 gal	37.9 L	10 gal	37.9 L	10 gal	37.9 L
Hydraulic tank capacity	18 gal	68.1 L	18 gal	68.1 L	18 gal	68.1 L
Weight(4) and Floor Loading(5)						
Weight	7,149 lb	3,243 kg	7,599 lb	3,447 kg	10,392 lb	4,714 kg
Weight with outriggers	7,535 lb	3,629 kg	8,449 lb	3,833 kg	11,242 lb	5,100 kg
Tire load max.	2,840 lb	1,288 kg	3,019 lb	1,369 kg	3,829 lb	1,737 kg
Tire contact pressure - front, platform fully extended	70.7 psi	487 kPa	75.1 psi	518 kPa	95.3 psi	657 kPa
Occupied floor pressure	170 psf	8.15 kPa	169 psf	8.11 kPa	215 psf	10.29 kPa
Sound and Vibration Levels						
Sound Pressure level (ground workstation)	85 dBA		85 dBA		85 dBA	
Sound Pressure level (platform workstation)	79 dBA		79 dBA		79 dBA	
Vibrations	< 8 ft 2 in/s²	< 2.5 m/s²	< 8 ft 2 in/s²	< 2.5 m/s²	< 8 ft 2 in/s²	< 2.5 m/s²



(1) The metric equivalent of working height adds 2 m to platform height. US adds 6 ft to platform height.
(2) Based on RT tires; deduct 2 in/5.8 cm for turf and non-marking tires.
(3) Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.
(4) Weight refers to standard configuration and may vary depending on options and/or country standards.
(5) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.

HireSafe SOLUTIONS

HONEST, RELIABLE & REACTIVE
SOLUTIONS FOR WORKING AT HEIGHT

CONTACT US
0800 865 4455
info@hiresafesolutions.com
www.hiresafesolutions.com

Genie® GS™-2669 RT, GS-3369 RT & GS-4069 RT

SKU: Standard Model

- **GS266901A30027:** GS-2669 RT
- **GS336901A30040:** GS-3369 RT
- **GS406901AF0043:** GS-4069 RT

* Build to Order

Option availability		S	S+	BtO
Power	24.8 hp, 18.5 kW Kubota D1105, Diesel, T4i/T4f, Stage IIIA/V, CN III		✔	
	28.5 hp, 21.3 kW, GM .998L, Gas/LPG			❍
	Cold weather package			❍
Platform	3kW AC Generator, 110V/50Hz			❍
	AC power to platform		✔	
	Air line to platform			❍
	Diamond plate platform deck		✔	
	Electronic horn		✔	
	Folding rails, Full-height swing gate		✔	
	Lanyard attachment points		✔	
	Platform control guard (PCON)		✔	
	Platform control with fault indicator		✔	
	Platform load sense system		✔	
	Proportional drive and lift		✔	
	Self-closing entry gate		✔	
	Single slide-out extension deck		✔	
Chassis	4 wheel drive		✔	
	Active oscillating axle		✔	
	Auto leveling hydraulic outriggers			❍
	Biodegradable hydraulic oil			❍
	Cold weather hydraulic oil			❍
	Descent, tilt and motion alarm		✔	
	Dual LED flashing beacons		✔	
	Dual wheel multi-disc brakes		✔	
	High floatation, foam filled tires (GS-2669, GS-3369)		✔	
	Lift Connect Telematics			❍
	Lift Connect with Access Manager upgrade			❍
	Rough Terrain, foam-filled tires		✔	
	Rough Terrain, foam-filled, non-marking tires			❍
	Tech Pro Link connector		✔	

- S Standard
- S+ Standard +
- BtO Build to Order
- ✔ Standard Features
- ❍ Options

4 Wheel Drive

Full Height Drive

Swing-Out Engine Tray

Genie Genuine Accessories(1)

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

HireSafe SOLUTIONS

HONEST, RELIABLE & REACTIVE
SOLUTIONS FOR WORKING AT HEIGHT

CONTACT US
0800 865 4455
info@hiresafesolutions.com
www.hiresafesolutions.com