

## MAKE THE MF 5700 M YOUR OWN AND AS INDIVIDUAL AS YOUR FARM

|  | MF 5710-13 M<br>12x12 | MF 5709-11 M<br>DYNA 4 |  | MF 5710-13 M<br>12x12 | MF 5709-11 M<br>DYNA 4 |
|--|-----------------------|------------------------|--|-----------------------|------------------------|
| <b>Engine</b>  |                       |                        | <b>Hydraulics</b>  |                       |                        |
| AGCO POWER 4 cylinders, Turbo, Common rail             | ●                     | ●                      | Independent auxiliary pump 58 l/min  | ●                     | ●                      |
| Memorised engine speed                                 | ●                     | ●                      | 2 Mechanical spool valves  | ●                     | ●                      |
| <b>Transmission</b>                                    |                       |                        | 3 Mechanical spool valves  | ○                     | ○                      |
| Mechanical 12x12                                       | ●                     | -                      | Lever linkage control (intermix)   | ●                     | -                      |
| Dyna-4 16x16   | -                     | ●                      | Advanced linkage control (intermix / max height / quick sol engagement / shock absorber) | ○                     | ●                      |
| Powershuttle   | ●                     | -                      | Linkage control on fender, left hand side  | -                     | ○                      |
| Comfort Control  | ●                     | -                      | Linkage control on fenders, both sides   | ●                     | ●                      |
| Power Control  | -                     | ●                      | Front linkage  | -                     | ○                      |
| De-clutch control on transmission lever                | ●                     | -                      | <b>PTO</b>   |                       |                        |
| AutoDrive & Brake to neutral                           | -                     | ○                      | Independent PTO  | ●                     | ●                      |
| Creeper  | ○                     | ○                      | Electro hydraulic PTO clutch   | ●                     | ●                      |
| Large cab flat floor (2 doors, easy access)            | ●                     | ●                      | In cab PTO speed selection   | ●                     | ●                      |
| Suspended Large cab flat floor (2 doors, easy access)  | -                     | ○                      | <b>Front axle</b>  |                       |                        |
| Fenders extensions                                     | ○                     | ○                      | 4WD  | ●                     | ●                      |
| Air conditioning                                       | ○                     | ○                      | Electro hydraulic diff lock  | ●                     | ●                      |
| High vis roof for loader operation                     | ○                     | ○                      | Front fenders*   | ○                     | ○                      |
| Dual Adjustment Steering Column (Tilting & Telescopic) | ●                     | ●                      | Pivoting front fenders   | ○                     | ○                      |
| Mechanical seat  | ●                     | ●                      | <b>Additional equipment</b>  |                       |                        |
| Pneumatic seat   | ○                     | ○                      | Hydraulic trailer brake (dual line)  | ●                     | ●                      |
| Passenger seat   | ○                     | ○                      | Pneumatic trailer brake (dual line)  | ○                     | ○                      |
| Radio/ CD / MP3/ Front Aux-in                          | ○                     | ○                      | Pneumatic trailer brake (dual line) + Hydraulic line                                     | ○                     | ○                      |
| Roof worklights (front & rear)                         | ●                     | ●                      | Isolator switch  | ●                     | ●                      |
| Additional handrails worklights                        | ○                     | ○                      |  |                       |                        |
| 2 rear view mirrors                                    | ●                     | ●                      |  |                       |                        |
| 2 rear view telescopic mirrors                         | ○                     | ○                      |  |                       |                        |
| Advanced performance monitor                           | ●                     | ●                      |  |                       |                        |
| Toolbox  | ●                     | ●                      |  |                       |                        |


- KEY**
- Standard specification
  - Optional
  - Not available

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

## DIMENSIONS

|   | MF 5710 M/<br>MF 5711 M<br>12x12 | MF 5709 M/<br>MF 5710 M/<br>MF 5711 M<br>DYNA-4 | MF 5712 M/<br>MF 5713 M<br>12x12 |
|---|----------------------------------|---|----------------------------------|
| A Overall length from front weight frame to rear linkage arms | 4,305                            | 4,305   | 4,305                            |
| B Wheelbase   | 2,430                            | 2,430   | 2,500                            |
| C Height to top of roof (standard/Visio)                      | 2,650*                           | 2,685*  | 2,730**                          |
| D Maximum ground clearance* (remove 80mm for pick-up hitch)   | 480                              | 515   | 520                              |
| E Height to top of roof (standard/Visio) from rear axle       |                                  | 1,949   |                                  |
| Width (min / max)   | 1,380-1,925                      | 1,795-2,587                                     | 1,795-2,587                      |
| Turning circle - external diameter, less brakes               | 8.3                              | 8.3   | 8.4                              |

\* 16.9 R 34 tyres \*\* 18.4 R 38 tyres †420/85R38 tyres



**HONEST, RELIABLE & REACTIVE**  
SOLUTIONS FOR WORKING AT HEIGHT



## CONTACT US

- ☎ 0800 865 4455
- ✉ info@hiresafesolutions.com
- 🌐 www.hiresafesolutions.com



|   | MF 5710 M<br>12x12   | MF 5711 M<br>12x12 | MF 5712 M<br>12x12                         | MF 5713 M<br>12x12  | MF 5709 M<br>Dyna 4   | MF 5710 M<br>Dyna 4 | MF 5711 M<br>Dyna 4 |          |          |          |           |         |          |          |
|---|--|--------------------|--|---|---|---------------------|---------------------|----------|----------|----------|-----------|---------|----------|----------|
| <b>Engine Performance</b>                     |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Nominal hp (kW) power @ 2200 rpm              | <table border="1"> <tr> <td>100 (77)</td> <td>110 (82)</td> <td>120 (90)</td> <td>130 (97)</td> <td>90 (68)</td> <td>100 (77)</td> <td>110 (82)</td> </tr> </table>  |                    |  |   |   |                     |                     | 100 (77) | 110 (82) | 120 (90) | 130 (97)  | 90 (68) | 100 (77) | 110 (82) |
| 100 (77)                                      | 110 (82)   | 120 (90)           | 130 (97)                                   | 90 (68)   | 100 (77)  | 110 (82)            |                     |          |          |          |           |         |          |          |
| Max hp (kW) power @ 2000 rpm                  | <table border="1"> <tr> <td>105 (80)</td> <td>115 (86)</td> <td>125 (93)</td> <td>135 (101)</td> <td>95 (71)</td> <td>105 (80)</td> <td>115 (86)</td> </tr> </table> |                    |  |   |   |                     |                     | 105 (80) | 115 (86) | 125 (93) | 135 (101) | 95 (71) | 105 (80) | 115 (86) |
| 105 (80)                                      | 115 (86)   | 125 (93)           | 135 (101)                                  | 95 (71)   | 105 (80)  | 115 (86)            |                     |          |          |          |           |         |          |          |
| Max torque @ 1500 rpm                         | <table border="1"> <tr> <td>440</td> <td>460</td> <td>520</td> <td>545</td> <td>405</td> <td>440</td> <td>460</td> </tr> </table>                                    |                    |  |   |   |                     |                     | 440      | 460      | 520      | 545       | 405     | 440      | 460      |
| 440   | 460  | 520                | 545  | 405   | 440   | 460                 |                     |          |          |          |           |         |          |          |
| <b>Engine</b>                                 | AGCO POWER 4.4 Liters, 4 cylinders   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Type/Capacity/no. of Cylinders                | Electronic injection, Common rail, 4 valves per cylinder, DOC + SCR  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Technology</b>                             |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Transmission</b>                           |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Type/No. of gears                             | 12x12<br>6x2   |                    |  | Semi Powershift 16x16<br>4x4  |   |                     |                     |          |          |          |           |         |          |          |
| Gears/ Ranges                                 | Power Shuttle (Comfort Control & Declutch button on lever) + Brake to Neutral (optional)   |                    |  | Power Shuttle (Power Control Lever & Comfort Control) + Brake to Neutral (optional) |   |                     |                     |          |          |          |           |         |          |          |
| Shuttle                                       | 1.26   |                    |  | 1.31  |   | 1.30                |                     |          |          |          |           |         |          |          |
| Min Speed @ 1400 rpm                          | 24x24  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Optional creeper gears                        | 0.09   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Min Speed @ 1400 rpm* with creeper            | 0.10   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Power Take-off</b>                         |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Operation and control                         | Independent/Electro hydraulic control  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Standard PTO speeds                           | 540 / 540Eco   |                    | 540 / 1000                                 |   | 540 / 540Eco  |                     |                     |          |          |          |           |         |          |          |
| Optional PTO speeds                           | 540 / 1000 // 540/540Eco/1000  |                    | 540 / 540Eco/1000 // 540 / 540Eco          |   | 540 / 1000 // 540/540Eco/1000   |                     |                     |          |          |          |           |         |          |          |
| PTO speed @ engine rpm                        | 2000   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| PTO speed @ engine rpm                        | 540 Eco<br>1550  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>PTO shaft</b>                              |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Standard                                      | 6 splines  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Optional                                      | 6 & 21 splines   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Hydraulics</b>                             |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Max oil flow - Stage 1                        | 33 l/min supplying steering brakes, diff lock, PTO, 4WD  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Standard max oil flow - Stage 2               | 58 l/min supplying spool valve and linkage   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Optional max oil flow - Stage 2               | 58 l/min supplying rear linkage + 42 l/min supplying spool valve   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Combined flow control                         | The two pumps can be combined to supply 100 l/min to spool valves (eg : Loader)  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Max pressure                                  | Fully automatic (Electrical switch in Cab)   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Standard spool valves / Optional spool valves | 200<br>2 / 3   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Rear linkage</b>                           |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Maximum lift capacity                         | 4,300  |                    | 5,200                                      |   | 4,300   |                     |                     |          |          |          |           |         |          |          |
| Lower links                                   | Hook ends (cat 2)  |                    | Hook ends (cat 3)                          |   | Hook ends (cat 2)   |                     |                     |          |          |          |           |         |          |          |
| <b>Brakes</b>                                 |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Type  | Electro hydraulic / Oil cooled   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Rear tyres</b>                             |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Standard                                      | 420/85 R 34  |                    | 420/85 R 38                                |   | 420/85 R 34   |                     |                     |          |          |          |           |         |          |          |
| Optional                                      | 460/85R34 - 480/70 R34 - 540/65R34<br>340/85 R 38 - 420/85 R 38<br>480/70 R 38 - 540/65 R 38   |                    | 460/85 R 38 -<br>520/70 R 38 - 600/65 R 38 |   | 460/85R34 - 480/70 R34 - 540/65R34<br>340/85 R 38 - 420/85 R 38 480/70 R 38 - 540/65 R 38 |                     |                     |          |          |          |           |         |          |          |
| <b>Capacities</b>                             |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| Fuel tank capacity                            | 153  |                    |  |   | 160   |                     |                     |          |          |          |           |         |          |          |
| AdBlue® tank capacity                         | 18   |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| <b>Weight</b>                                 |  |                    |  |   |   |                     |                     |          |          |          |           |         |          |          |
| 4WD**   | 4,070  |                    | 4,230                                      |   | 4,400   |                     | 4,500               |          |          |          |           |         |          |          |

**KEY**  
 ⚙ ISO TR14396  
 \* Manufacturer's testing  
 \*\* Standard configuration with full fuel tanks, an operator - 75 kg and the smallest tyres



**HONEST, RELIABLE & REACTIVE**  
 SOLUTIONS FOR WORKING AT HEIGHT



**CONTACT US**

☎ 0800 865 4455  
 ✉ info@hiresafesolutions.com  
 🌐 www.hiresafesolutions.com

